

MAX ATF®

Automatic Transmission Fluid



Beyond Synthetic™

Max ATF® is a synthetic, high performance, long life, multipurpose, automatic transmission fluid. Max ATF® is recommended for all automatic transmissions requiring Ford Mercon® or GM Dexron® III transmission fluids. Max ATF® is much more oxidation stable than other transmission fluids and greatly resists breakdown from heat and loss of proper lubricity. Max ATF® is fully compatible and can be mixed with other automatic transmission fluids; however, for the best results drain old oil and then fill with Max ATF®.

Performance Advantages:

- Greater Wear Protection
- Longer Fluid Life
- Clean, Efficient Equipment
- Greatly Extended Equipment Life
- Much Longer Oil Life
- Outstanding Rust/Corrosion Protection
- Smoother Shifting
- Reduced Temperatures

Typical Properties*

Viscosity	
cSt @ 40°C	32.5
cSt @ 100°C	7.5
SSU @ 100°F	164
SSU @ 210°F	51
cP @ -10°C (14°F)	332
cP @ -20°C (-4°F)	664
cP @ -30°C (-22°F)	1491
cP @ -40°C (-40°F)	3852
Viscosity Index	210
Pour Point	-60
Flash °F	450
Fire °F	490
Foam Test	
Sequence I	0 ml / 0 ml
Sequence II (4 sec.)	10 ml / 0 ml
Density	
Specific Gravity @60°F	0.838
Pounds/Gallon	6.98
Copper Corrosion	
3 hrs. @ 210°F	1a

*All properties are typical and may vary.